

Sredstvo za učvršćivanje površine

- *Površinsko učvršćivanje i dubinska zaštita betona i cementnih materijala*
- *Tečnost spremna za upotrebu*

OPIS PROIZVODA

Tečnost spremna za upotrebu, strukturalna solidifikacija, na bazi silikata.

PODRUČJA PRIMENE

Za upotrebu na betonskim ili cementnim površinama.

OSOBINE

VANDEX MINERALIT kroz fiziološko-hemijski proces proizvodi poboljšanje površinske strukture cementnih građevinskih materijala. Kristalizacija nastala od visokog sadržaja silicijumskih kiselina proizvodi jedinjenja koja mogu poboljšati jačinu i gustinu podloge.

PRIPREMA POVRŠINE

Površina mora biti čista, bez bilo kakve prljavštine i prašine. Podloga koja se tretira mora biti glatka i ravna, takođe mora biti suva u trenutku nanošenja materijala.

NANOŠENJE

Naneti VANDEX MINERALIT u 1 do 2 sloja. Prilikom nanošenja koristiti četku ili sprej sa slabim pritiskom.

POTROŠNJA

U zavisnosti od poroznosti površine, potrošnja uobičajeno iznosi između 150–250 ml/m². Precizne količine moraju biti određene probnom aplikacijom.

PAKOVANJE

10 l - kontejner

SKLADIŠTENJE

Može se skladištiti na mestima bez mraza. Kada se čuva neotvoren, neoštećen u originalnom pakovanju, rok trajanja je 24 meseca.

BEZBEDNOST I ZDRAVLJE

VANDEX MINERALIT je alkalno jedinjenje. Izbegavati kontakt sa licem i očima. Nosite odgovarajuće rukavice i zaštitu za lice/oči. Ukoliko dodje do kontakta sa kožom odmah dobro isperite sa dosta vode. U slučaju kontakta sa očima odmah isprati sa puno vode i potražiti lekarsku pomoć. Za detaljnije informacije pogledati bezbednosni list na veb stranici www.vandex.com.

TEHNIČKI PODACI	
Izgled	bistra vodena tečnost
Boja	bezbojan
Gustina na 20 °C	[kg/l] oko. 1.14
PH vrednost	oko. 11.5
All data are averages of several tests under laboratory conditions. In practice, climatic variations such as temperature, humidity, and porosity of substrate may affect these values.	

The information contained herein is based on our long-term experience and the best of our knowledge. We can, however, make no guarantee since for a successful outcome, all circumstances in an individual case must be taken into consideration. Indications of quantities required are only averages which in certain cases might be greater.

Vandex[®]
CONCRETE

An **RPM** Company

PROTECTION AND WATERPROOFING

HEADOFFICE AND INTERNATIONAL SALES:
VANDEX INTERNATIONAL LTD
P.O. Box, CH-4501 Solothurn/Switzerland
Phone: +41 32 626 36 36, Fax +41 32 626 36 37
E-mail: info@vandex.com
www.vandex.com

PRODUCTION AND SALES GERMANY/AUSTRIA:
VANDEX ISOLIERMITTEL-GESELLSCHAFT m.b.H.
P.O. Box, 1406, D-21487 Schwarzenbek/Germany
Phone: +49 4151 89 15-0, Fax +49 4151 89 15 50 E-mail:
info@vandex.de www.vandex.de

